

TECHNICALS SPECIFICATIONS




Image for guidance purposes.

Model:

AKD-650

Gen set composed of engine and alternator perfectly assembled and fitted in a practical tubular chasis, that is adding great strenght and versatility.

STANDBY POWER (LTP):
(LTP: "Limited Time Power" norma ISO 8528-1)

7 kVA

Engine

Make	Kohler
Model	KD15-440
Fuel	Diesel
Start	Electric with battery
Cooling system	Air

Mechanical effect power (kWm)	6,7
Diameter x stroke (mm)	86x76
Compresion ratio	20,3:1
Series regulator	M
No. cylinders	1
Displacement (cm ³)	441
Fuel consumption 100% (L/H)	2
Oil tank capacity (L)	1,5
Máx. oil consumption (kg/h)	0,0048
Battery recommended V/Ah	12/19
Fuel tank capacity (L)	5

Alternator

Voltage (V)	400 / 230
Frequency (Hz)	50
R.p.m.	3000
No. poles	2
Protection degree IP	21
Insulation	H

*Series regulator M: Mechanical.

Genset general characteristics

Prime Power PRP (kVA/kW)	6,5
Standby power LTP (kVA)	7
Frequency (Hz)	50
R.p.m.	3000
Voltage (V)	400 / 230
Cos Φ	1

Dimensions and weight

Dimensions (mm) Lenght x Width x Height	810x550x600
Weight (kg)	117

OPTIONS

- Control panel with voltmeter & hours counter or ammeter.
- Control panel equipped with DSE 3110 for remote start
- Transport kit with wheel and handles

Sockets description:

- 1 TRIPHASE CEE SOCKET
- 1 MONOPHASE SCHUKO SOCKET 16 A and termic protections.